



Designed for:	Attaching hardware to unreinforced PVCU
Head Style:	Countersunk
Drive Bit:	SQ1 for installation. PH2 for on-site adjustment
Thread Form:	Single Deep Thread
Point:	Fast Starting Gimlet Point
Salt Spray Testing	1000 Hours in accordance with BS EN 9227:2012
Corrosion protection;	Grade 5 acc. to BS EN 1670:2007
Shank Material:	Austenitic Stainless Steel
Material Grade:	302
Effective Thread Length:	Fully Threaded

Product Code	Size – Shank x NL	HD	Box Quantity
CFG 4.3 x 16 CS	4.3mm x 16.0mm	6.75mm ± 0.25mm	1000
CFG 4.3 x 20 CS	4.3mm x 20.0mm	6.75mm ± 0.25mm	1000
CFG 4.3 x 25 CS	4.3mm x 25.0mm	6.75mm ± 0.25mm	1000
CFG 4.3 x 30 CS	4.3mm x 30.0mm	6.75mm ± 0.25mm	1000
CFG 4.3 x 45 CS	4.3mm x 45.0mm	6.75mm ± 0.25mm	1000



Rapierstar Limited
Star Business Park, Macclesfield, Cheshire SK11 9JA
Tel: +44(0)1260 223311 Fax: +44(0)1260 223399
email: info@rapierstar.com

www.rapierstar.com

