



Designed for:	Attaching Hardware to Reinforced PVCU
Head Style:	Countersunk with Locking Ribs
Recess:	Combination SQ1/PH2
Drive Bit (Installation):	SQ1
Drive Bit (On-Site Adjustment)	PH2
Thread Form:	Self-Tapping
Point:	Drill Point
Coating:	Inorganic Anti-Corrosion Coating
Salt Spray Testing (Drill Point):	250 Hours Minimum in accordance with BS EN 9227:2012
Salt Spray Testing (Shank):	1000 Hours in accordance with BS EN 9227:2012
Corrosion Protection:	Grade 5 acc. to BS EN 1670:2007
Shank Material:	Austenitic Stainless Steel
Drill Point Material:	Carbon Steel
Material Grade: (Shank)	302
Material Grade: (Drill Point)	AISI C1022
Effective Thread Length:	Fully Threaded

Product Code	Size – Shank x NL	HD	Box Quantity
CSR 4.5 x 18 CB	4.5mm x 18.0mm	6.95mm ± 0.15mm	1000
CSR 4.5 x 23 CB	4.5mm x 23.0mm	6.95mm ± 0.15mm	1000
CSR 4.5 x 25 CB	4.5mm x 25.0mm	6.95mm ± 0.15mm	1000
CSR 4.5 x 32 CB	4.5mm x 32.0mm	6.95mm ± 0.15mm	1000
CSR 4.5 x 38 CB	4.5mm x 38.0mm	6.95mm ± 0.15mm	500



Rapierstar Limited
Star Business Park, Macclesfield, Cheshire SK11 9JA
Tel: +44(0)1260 223311 Fax: +44(0)1260 223399
email: info@rapierstar.com

www.rapierstar.com

