



Designed for:	Attaching Friction Stays to Reinforced Profile
Head Style:	Shallow Pan
Drive Bit:	PH2
Thread Form:	Spaced Self-Tapping
Point:	Drill Point
Coating:	Electroplated Yellow or Zinc plus Passivation
Salt Spray Testing:	Minimum 250 Hours in accordance with BS EN 9227:2012
Corrosion Protection:	Grade 4 acc. to BS EN 1670:2007
Shank Material:	Carbon Steel
Material Grade:	AISI C1022
Effective Thread Length:	Fully Threaded

Product Code	Size – Shank x NL	HD	Box Quantity
SSR 3.9 x 16 Z	3.9mm x 16.0mm	8.10mm ± 0.20mm	1000
SSR 3.9 x 19 Y or Z	3.9mm x 19.0mm	8.10mm ± 0.20mm	1000
SSR 3.9 x 25 Z	3.9mm x 25.0mm	8.10mm ± 0.20mm	1000
SSR 3.9 x 28 Z	3.9mm x 28.0mm	8.10mm ± 0.20mm	1000



Rapierstar Limited
Star Business Park, Macclesfield, Cheshire SK11 9JA
Tel: +44(0)1260 223311 Fax: +44(0)1260 223399
email: info@rapierstar.com

www.rapierstar.com

