



<b>Designed for:</b>	Attaching Friction Stay Hinge to unreinforced PVCU
<b>Head Style:</b>	Ultra-Low Shallow Pan
<b>Drive Bit:</b>	PH2
<b>Thread Form:</b>	Single Deep Thread
<b>Point:</b>	Fast Starting Gimlet Point
<b>Coating:</b>	Electroplated Zinc plus Clear Passivation
<b>Salt Spray Testing:</b>	Minimum 250 Hours in accordance with BS EN 9227:2012
<b>Corrosion Protection:</b>	Grade 4 acc. to BS EN 1670:2007
<b>Shank Material:</b>	Carbon Steel
<b>Material Grade:</b>	AISI C1018
<b>Effective Thread Length:</b>	Fully Threaded

### LFG Mechanical Data\*

Product Code	Size – Shank x NL	HD	Max Recommended Tightening Torque*	EAN Code	Box Quantity
LFG 4.3 x 16 Z	4.3mm x 16.0mm	8.10mm± 0.20mm	2.75 Nm	5055159023832	1000
LFG 4.3 x 20 Z	4.3mm x 20.0mm	8.10mm± 0.20mm	2.75 Nm	5055159023849	1000
LFG 4.3 x 25 Z	4.3mm x 25.0mm	8.10mm± 0.20mm	2.75 Nm	5055159023856	1000
LFG 4.3 x 30 Z	4.3mm x 30.0mm	8.10mm± 0.20mm	2.75 Nm	5055159036177	1000
LFG 4.8 x 20 Z	4.8mm x 20.0mm	8.10mm± 0.20mm	4.0 Nm	5055159036184	1000
LFG 4.8 x 25 Z	4.8mm x 25.0mm	8.10mm± 0.20mm	4.0 Nm	5055159036191	1000
LFG 4.8 x 30 Z	4.8mm x 35.0mm	8.10mm± 0.20mm	4.0 Nm	5055159036207	1000

\*Figures are typical values. It is recommended that any user carries out appropriate testing and applies a suitable safety factor as necessary.



Rapierstar Limited  
Star Business Park, Macclesfield, Cheshire SK11 9JA  
Tel: +44(0)1260 223311 Fax: +44(0)1260 223399  
email: sales@rapierstar.com

[www.rapierstar.com](http://www.rapierstar.com)

